

Suitable for the control of general heating and lighting loads in AC installations.

- ✔ 230V 50Hz coil voltage.
- ✔ Contact configurations refer to the ordering data.
- ✔ Selection based on the type of load, refer to the technical data for specific duty ratings.



Ordering reference: see below

Product Standard: EN60947-3

HS20 - Contactor 230V 50Hz coil (Ith = 20A)**

Modules	*Poles		Switching Voltage	Reference
	NO	NC		
1		2	230	HS 20-02
1	1	1	230	HS 20-11
1	2		230	HS 20-20



HS20-11

HS25 - Contactor 230V 50Hz coil (Ith = 25A)**

Modules	*Poles		Switching Voltage	Reference
	NO	NC		
2		4	230	HS 25-04
2	2	2	230	HS 25-22
2	3	1	230	HS 25-31
2	4		230	HS 25-40



HS25-31

HS40-** Contactor 230V 50Hz coil (Ith = 40A)				
Modules	*Poles		Switching Voltage	Reference
	NO	NC		
3	4		230	HS 40-04
3	2	2	230	HS 40-22
3	3	1	230	HS 40-31
3	4		230	HS 40-40
2	2		230	HS 40-20S



HS40-04

HS40-20S

HS63-** Contactor 230V 50Hz coil (Ith = 63A)				
Modules	*Poles		Switching Voltage	Reference
	NO	NC		
3	2	2	230	HS 63-22
3	3	1	230	HS 63-31
3	4		230	HS 63-40
2	2		230	HS 63-20S



HS63-31

HS-63-20S

Have a question? Please contact us today

Tel: 01628 829133 email: sales@doepke.co.uk

Doepke UK Ltd